




Ming Feng Lighting Co.,Ltd

Address: Building 2, Zao San Street 5th,Dongcheng District, Dongguan City, Guangdong province,P.R.China.

Tel: +86-769-2332-0862

Fax:+86-769-2203-6052

Email: Sales@mingfeng-lighting.com



MF-PF Family LED Panel Light Data Sheet

Item No.

MF-PF

Lighting Data

Electrical Data

LED Type	Epistar EPISTAR	Power Supply	CE / LIFUD LIFUD
System Efficacy	90lm/W and 110LM/W	Input Voltage	100~240V ac
System Power Consumption	36W/42W/48W	Power Frequency	50~60Hz
CCT	2700K,3000K, 4000K, 5000K	Output Voltage	28.8~48VDC
Beam Angle	120°	Output Current	2.0A(Constant Current)
CRI	Ra80 / Ra 90	Power Efficiency	>90%
System Efficiency	>90%	Power Factor	>0.90
SDCM	<5	Total Harmonic Distortion	<20%

Material Data

Packing Data

Fixture Material	Aluminum+PC	Junction Temperature(Tj)	<70°C(Ta=30°C)
Paintings	AkzoNobel	Storage Temperature	-40~+85°C
Cable	2x0.75mm	Operating Temperature	-25~+50°C
Ingress Protection	IP20	Outlook Size(ft)	2x2 ft, 2x4 ft
Plug socket	Click-in system	Cutting Size(MM)	N/A
Life Span	7 years at 12 hours/day	Export Carton Size	Refer to specified data sheet

Optional Info.

Installation Method	Recessed/Surface/Suspend	Certificates	
Fixture Color	White		
Intelligent Control	1~10V Dim/Triac/DALi control		

Job Reference

Light Distribution Curve

