



Ming Feng Lighting Co.,Ltd

Address: Building 2, Zao San Street 5th,Dongcheng District, Dongguan City,Guangdong province,P.R.China.

Tel: +86-769-2332-0862

Fax:+86-769-2332-0862

Email: Sales@mingfeng-lighting.com



MF LED Tri-proof Light Data Sheet

Item No.

MF12-600~MF24-600,MF54-1560


Lighting Data

Electrical Data







LED Type	Epistar	Power Supply	LiFud
System Efficacy	100lm/W±5%(CCT=5000K)	Input Voltage	85~265Vac
System Power Consumption	12W ~ 54W	Power Frequency	50~60Hz
CCT	2700K,3000K, 4000K, 5000K	IK Protecions	IK08-IK10 resistance
Beam Angle	120°	Class Rate	Class I
CRI	Ra80/Ra90+	Power Efficiency	>90%
System Efficiency	>90%	Power Factor	>0.90
SDCM	<5	Total Harmonic Distortion	<20%

Material Data

Packing Data

Fixture Material	Alu.alloy+PC	Junction Temperature(Tj)	<70°C(Ta=30°C)
Paintings	AkzoNobel 	Storage Temperature	-40~+70°C
Cable	3x0.75mm	Operating Temperature	-30~+50°C
Ingress Protection	IP65	Length(MM)	600, 1200,1500
Plug socket	Click-in system	Cutting Size(MM)	None
Life Span	10 years at 12 hours/day	Export Carton Size	Refer to specified data sheet

Optional Info.

Installation Method	Suspended /Ceiling	Certificate			
Fixture Color	White				
Intelligent Control	1~10V Dim/DALi control				

Job Reference

Light Distribution Curve

