



Ming Feng Lighting Co.,Ltd

Address: Building 2, Zao San Street 5th,Dongcheng District,
Dongguan City,Guangdong province,P.R.China.
Tel: +86-769-2332-0862 **Fax:**+86-769-2203-6052
Email: Sales@mingfeng-lighting.com



MF-TD833F LED Spot Light Data Sheet

Item No.

MF-TD833F

Lighting Data

Electrical Data

LED Type	Citizen ●CITIZEN	Power Supply	Lifud LiFuD
System Efficacy	100lm/W±5%	Input Voltage	100~240V ac
System Power	7W/13W	Power Frequency	50~60Hz
CCT	2700K,3000K, 4000K, 5000K	Output Voltage	28.8~48VDC
Beam Angle	15°/24°/38°/60°	Output Current	2.0A(Constant Current)
CRI	Ra80 /Ra 90	Power Efficiency	>90%
System Efficiency	>90%	Power Factor	>0.90
SDCM	<5	Total Harmonic Distortion	<20%

Material Data


Packing Data

Fixture Material	Alu.alloy+PC	Junction Temperature (Tj)	<70°C(Ta=30°C)
Paintings	AkzoNobel	Storage Temperature	-40~+60°C
IP Rate	IP20	Operating Temperature	-40~+40°C
Ingress Protection	N/A	Outlook Size(MM)	86mm
Dimmable	N/A	Cutting Size(MM)	75mm
Life Span	7 years at 12 hours/day	Export Carton Size	Refer to specified data sheet

Senior Info.

Installation Method	Recessed Mount
Fixture Color	White and Black
Intelligent Control	N/A
Adjustable	360°

Certificates



Job Reference

Light Distribution Curve

